

Product Code 15-A132-05-08 Installation Instructions 3D File Photometry Dialux | ULD



## Levels 1 Body Ø320mm

Nahtrang Design

Ceiling fixture Levels 1 Body Ø320mm LED 28 SW 2700-3000-4000K PHASE CUT Black 1850lm

#### Technical features

Luminaire total power: 28W Real lumens: 1850 (3000K)

Real Im/W: 66

Correlated Colour Temperature (CCT): SW 2700-3000-4000K

Lens / reflector angle: HORIZONTAL 101°

Structure material: Steel Structure finish: Black Diffuser material: Glass Diffuser finish: Green Driver Brand: HEP

Voltage / frequency: 220-240V/50-60Hz

Dimming protocol: PHASE CUT

Power Factor: NULL

Useful life: 50,000h L80B20

Warranty: 5 años

Easily recyclable luminaire









### Luminotechnic features

CRI: 90

MacAdam steps: 3

Photobiological risk: RG1

Lampholder	Quantity	Light source power (W)
LED	1	24.4W






Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.



Product Code 15-A132-05-08 Installation Instructions 3D File Photometry Dialux | ULD



# Levels 1 Body Ø320mm

Nahtrang Design

Ceiling fixture Levels 1 Body Ø320mm LED 28 SW 2700-3000-4000K PHASE CUT Black 1850lm

### Logistics



Net weight (kg): 2.16

Packaged weight (kg): 3.03

Packaging: 425mm x 410mm x 270mm

Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.