Product Code 15-A135-05-08 Installation Instructions 3D File Photometry Dialux | ULD



Levels Ceiling 2 Bodies Ø420mm + Ø320mm

Nahtrang Design

Ceiling fixture Levels Ceiling 2 Bodies Ø420mm + Ø320mm LED 28 SW 2700-3000-4000K PHASE CUT Black 1850lm

Technical features

Luminaire total power: 28W Real lumens: 1850 (3000K)

Real Im/W: 66

Correlated Colour Temperature (CCT): SW 2700-3000-4000K

Lens / reflector angle: HORIZONTAL 101°

Structure material: Steel Structure finish: Black Diffuser material: Glass Diffuser finish: Green Driver Brand: HEP

Voltage / frequency: 220-240V/50-60Hz

Dimming protocol: PHASE CUT

Power Factor: NULL

Useful life: 50,000h L80B20

Warranty: 5 años

Easily recyclable luminaire











Luminotechnic features

CRI: 90

MacAdam steps: 3

Photobiological risk: RG1

Lampholder	Quantity	Light
		source
		power
		· (W)
LED	1	24.4W






Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.



Product Code 15-A135-05-08 Installation Instructions 3D File Photometry Dialux | ULD



Levels Ceiling 2 Bodies Ø420mm + Ø320mm

Nahtrang Design

Ceiling fixture Levels Ceiling 2 Bodies Ø420mm + Ø320mm LED 28 SW 2700-3000-4000K PHASE CUT Black 1850lm

Logistics

Net weight (kg): 4.3

Packaged weight (kg): 6.43

Packaging: 1020mm x 610mm x

420mm

Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.