

Product Code 15-A144-05-08 Installation Instructions 3D File Photometry Dialux | ULD



# Levels 1 Body Ø320mm

Nahtrang Design

Ceiling fixture Levels 1 Body Ø320mm LED 28 SW 2700-3000-4000K CASAMBI Black 1850lm

#### Technical features Luminaire total power: 28W Real lumens: 1850 (3000K)

Real lumens: 1850 (3000K) Real lm/W: 66 Correlated Colour Temperature (CCT): SW 2700-3000-4000K Lens / reflector angle: HORIZONTAL 101° Structure material: Steel Structure finish: Black Diffuser material: Glass Diffuser finish: Green Voltage / frequency: 110-277V/50-60Hz Dimming protocol: CASAMBI Power Factor: NULL Useful life: 50,000h L80B20 Warranty: 5 años Easily recyclable luminaire



### Luminotechnic features

CRI: 90 MacAdam steps: 3

Photobiological risk: RG1

Lampholder	Quantity	Light source power (W)
LED	1	24.4W

200   Ø320	

Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.



Product Code 15-A144-05-08 Installation Instructions 3D File Photometry Dialux | ULD




# Levels 1 Body Ø320mm

Nahtrang Design

Ceiling fixture Levels 1 Body Ø320mm LED 28 SW 2700-3000-4000K CASAMBI Black 1850lm

#### Bluetooth range



The Bluetooth range largely depends on the obstacles and architectural features of a space, such as walls and building materials

## Logistics



Net weight (kg): 2.49 Packaged weight (kg): 3.36 Packaging: 425mm x 410mm x 270mm

Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.