

FRS 20



Energy-saving marvels for many different places.

The new FRS-20-light combines sensor-technology, low-energy light source and ultra slimline design. The result – a light for unlimited of different uses.

Settings

- Infinitely variable, electronic reach setting from Ø 1 – 5 metres.
- Easy adjustment of light "ON" time and twilight threshold by control dial.

Operational reliability


- Bulbs work independently of each other (so light stays "ON" even if one of the bulbs is faulty).



Main features at a glance



Angle of coverage: 360°



Detection zone when wallmounted



Detection zone when ceilingmounted



Twilight setting



Time setting

FRS 20**EAN white**

Dimensions (hxwxd)

Output

Voltage

Angle of coverage

Transmitter power

HF system

Reach

Twilight setting

Time setting

Enclosure

Protection class

Impact-resistant

4007841 743512

300 x 195 x 63 mm

only 2 x 11 W / 2G7 (bi-tube low-energy bulb), additional switching capacity 200 W max. / e.g. bathroom / WC extractor fan

230 – 240 V, 50 Hz

360° with 160° aperture angle also through glass, wood and stud walls

approx. 1 mW

5,8 GHz

1 – 5 m dia., infinitely variable

2 - 2000 lux

5 sec. – 15 min.

IP 44

II

IK 7

Subject to technical modifications.