

Product Code 00-6021-27-27 Installation Instructions 3D File Revit (BIM)



Candle Triplex

Benedito Design

Pendant Candle Triplex LED 11.5 LED warm-white 2700K PHASE CUT Brass 461lm

Technical features Luminaire total power: 11.5W Real lumens: 461 Real Im/W: 40 Correlated Colour Temperature (CCT): LED warm-white 2700K Structure material: Steel, Aluminium Structure finish: Brass Diffuser material: Methacrylate Diffuser finish: Transparent **Driver Brand: HEP** Voltage / frequency: 220-240V/50-60Hz Ø218 Dimming protocol: PHASE CUT Power Factor: 0.90 THD%: 20 Useful life: 50,000h L80B20 Max. Warranty: 5 años 2000 210 G ^At IP20 (\pm) 316 Luminotechnic features $\overline{@25}$ CRI: 90 MacAdam steps: 2 Photobiological risk: RG1 Light source Lampholder Quantity power (W) LED 9.4W

Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.



Product Code 00-6021-27-27 Installation Instructions 3D File Revit (BIM)



Candle Triplex

Benedito Design

Pendant Candle Triplex LED 11.5 LED warm-white 2700K PHASE CUT Brass 461lm

Logistics



Net weight (kg): 3.05 Packaged weight (kg): 4.46 Packaging: 750mm x 320mm x 260mm

Light application



Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.