Product Code 00-8304-05-M1

Installation Instructions
3D File
Photometry
Dialux | ULD
Revit (BIM)



Dew Vertical 992mm

Yonoh

Pendant Dew Vertical 992mm LED 13 LED warm-white 2700K DALI Black 782lm

Technical features

Luminaire total power: 13W

Real lumens: 782 Real lm/W: 60

Correlated Colour Temperature (CCT): LED warm-white 2700K

UGR: <=19

Structure material: Aluminium

Structure finish: Black

Diffuser material: Polycarbonate

Diffuser finish: Opal white Driver Brand: MEAN WELL

Voltage / frequency: 220-240V/50-60Hz

Dimming protocol: DALI Power Factor: 0.94

THD%: 20

Useful life: 50,000h L80B20

Warranty: 5 años









Luminotechnic features

Luminance C0°G65°: 2359 Luminance C90°G65°: 2320


CRI: 90

MacAdam steps: 3

Photobiological risk: RG1

UGR		
S=0.250		
Ceiling / cavity	0.7	
Walls	0.5	
Working Plane	0.2	
Room dimensions	X=4H, Y=8H	
UGR crosswise	17.9	
UGR lengthwise	17.8	

Lampholder	Quantity	Light source power (W)
LED	1	10.5W






Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.



Product Code 00-8304-05-M1

Installation Instructions
3D File
Photometry
Dialux | ULD
Revit (BIM)



Dew Vertical 992mm

Yonoh

Pendant Dew Vertical 992mm LED 13 LED warm-white 2700K DALI Black 782lm

Logistics

Net weight (kg): 1.1

Packaged weight (kg): 2.57 Packaging: 225mm x 100mm x

1235mm

Light application



Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.