

Data sheet



Sensor-switched outdoor light

L 585 S

black

EAN 4007841005535



Function description

Individualist all round. Outdoor SensorLight L 585 S, ideal for building fronts and entrances, 180° angle of coverage, reach up to 12 m, selectable time and twilight threshold, sensor tilts through 70° for exact adjustment of the detection zone.

Technical specifications

| | |
|---|--------------------------------|
| Dimensions (L x W x H) | 307 x 215 x 228 mm |
| Mains power supply | 230 – 240 V , 50 / 50 Hz |
| Sensor Technology | passive infrared |
| Output | 60 W |
| With lamp | No |
| Lamp | All-purpose lamp |
| Base | E27 |
| With motion detector | Yes |
| Detection angle | 180 ° |
| Sneak-by guard | Yes |
| Capability of masking out individual segments | Yes |
| Electronic scalability | No |
| Mechanical scalability | No |
| Reach, radial | r = 3 m (14 m ²) |
| Reach, tangential | r = 12 m (226 m ²) |
| Photo-cell controller | Yes |
| Twilight setting | 2 – 2000 lx |
| Time setting | 8 sec – 35 min |

Data sheet



Sensor-switched outdoor light

L 585 S

black

EAN 4007841005535

Technical specifications

| | |
|--------------------------------|-------------------|
| IP rating | IP44 |
| Protection class | II |
| Ambient temperature | -20 – 40 °C |
| Housing material | Plastic |
| Cover material | Glass transparent |
| Manufacturer's Warranty | 3 years |
| Version | black |
| PU1, EAN | 4007841005535 |

Mood image

