

Product Code 05-0070-14-14

Installation Instructions
3D File
Photometry
Dialux | ULD
Revit (BIM)



Oval 180mm

Wall fixture Oval 180mm LED 6.1 LED warm-white 3000K ON-OFF White 340lm

Technical features

Luminaire total power: 6.1W

Real lumens: 340 Real lm/W: 56

Correlated Colour Temperature (CCT): LED warm-white 3000K

UGR: <=22

Structure material: Aluminium, Steel

Structure finish: White Driver Brand: HEP

Voltage / frequency: 100-240V/50-60Hz

Dimming protocol: ON-OFF

Power Factor: 0.90

Useful life: 50,000h L80B20

Warranty: 5 años

Easily recyclable luminaire











Luminotechnic features

CRI: 90

MacAdam steps: 3

Photobiological risk: RG1

UGR crosswise: 16.1 UGR lengthwise: 24.4

	Lampholder	Quantity	Light source power (W)
I	LED	1	4.8W






Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.



Product Code 05-0070-14-14

Installation Instructions
3D File
Photometry
Dialux | ULD
Revit (BIM)



Oval 180mm

Wall fixture Oval 180mm LED 6.1 LED warm-white 3000K ON-OFF White 340lm

Logistics	Logi	isti	ics
-----------	------	------	-----

12 x 12

Net weight (kg): 0.6

Packaged weight (kg): 0.74

Packaging: 205mm x 90mm x 120mm

Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.