

Product Code 05-7983-05-F9

Installation Instructions 3D File Photometry Revit (BIM)



Dresde Led

Nahtrang Design

Bath IP44 Dresde Led LED 10.5 LED warm-white 3000K ON-OFF Black 563lm

Technical features

Luminaire total power: 10.5W

Real lumens: 563 Real lm/W: 54

Correlated Colour Temperature (CCT): LED warm-white 3000K

Structure material: Aluminium

Structure finish: Black
Diffuser material: Glass
Diffuser finish: Sandblasted

Voltage / frequency: 100-240V/50-60Hz

Dimming protocol: ON-OFF

Power Factor: 0.90

Useful life: 50,000h L80B20

Warranty: 5 años

Easily recyclable luminaire













Luminotechnic features

CRI- 90

MacAdam steps: 3

Photobiological risk: RG2 UGR crosswise: 20.5 UGR lengthwise: 16.4

Lampholder	Quantity	Light source power (W)
LED	1	9W






Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.



Product Code 05-7983-05-F9

Installation Instructions 3D File Photometry Revit (BIM)



Dresde Led

Nahtrang Design

Bath IP44 Dresde Led LED 10.5 LED warm-white 3000K ON-OFF Black 563lm

Logistics

x 8

Net weight (kg): 0.54

Packaged weight (kg): 0.91

Packaging: 220mm x 120mm x

290mm

Light application



Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.