



Kössel Direct Wall fixture

Description

Wall light for outdoor use.

For frontal lighting. Specially designed to conceal all mounting screws. Includes easily interchangeable decorative front panels in various finishes. Suitable for installation in marine environments. Includes 2 cable outlets to facilitate chain mounting. Structure material: Polycarbonate + ABS. Structure finish: Grey. Diffuser material: Polycarbonate. Diffuser finish: Prismatic. UV protection. Warranty: 5 Years.

Finish
Grey
Prismatic

Material
Polycarbonate + ABS
Polycarbonate

IP65 IK10   36

TECHNICAL CHARACTERISTICS

Light source
Light source: LED HANGKE
Output (W): 4W
Total power consumption (W): 4
Color temperature: LED neutral-white 4000K
CRI: 80
Photobiological risk: RG0
Real Lumen: 291
Qty Leds: 44
Lm/Real W: 73
Life Time: 50.000h L80B20
Bin / Grup: 4000K
MacAdam steps: 3
UGR: 19.2

GEAR
Brand: DRIVER AC
Gear included: Yes, electronic
Voltage / Frequency: 220-240/50-60Hz

Luminaire
Double cable exit: Yes
Drainage: No
Seaside: Yes
Uv Protection: Yes
Warranty: 5 Years

Logistics
Energy Efficiency: LED A++
EAN Code: 8435381435523
Net Weight (Kg): 0.310
Weight in Kg (packaged): 0.400
Packing: 240 x 95 x 75
Masterbox: 36

The photograph may not match the reference exactly. Please read the product description to identify the finish.

