



## PRODUCT SPECIFICATION

### GENERAL

|                                  |                         |                        |                          |
|----------------------------------|-------------------------|------------------------|--------------------------|
| <b>FINISH:</b>                   | Matt White              | <b>CABLE LENGTH:</b>   | Not Applicable           |
| <b>MAIN MATERIAL:</b>            | Metal - Mild Steel      | <b>GROSS WEIGHT:</b>   | 0.39 (Kg)                |
| <b>DIMENSIONS:</b>               | H: 65mm W: 65mm D: 42mm | <b>CLASS:</b>          | CE (Class III)           |
| <b>INSTALLATION ORIENTATION:</b> | Wall Mount - Vertical   | <b>IP RATING:</b>      | IP20                     |
| <b>CUT OUT HOLE:</b>             | H: 115mm H: 67mm        | <b>BATHROOM ZONE:</b>  | Zone 3                   |
| <b>RECESS DEPTH:</b>             | 42                      | <b>VOLTAGE:</b>        | Constant Current 700(mA) |
| <b>FIRE RATING:</b>              | Not Applicable          | <b>PRODUCT F MARK:</b> | Not Applicable           |

### LAMP


|                             |                |                                   |                |
|-----------------------------|----------------|-----------------------------------|----------------|
| <b>LIGHT SOURCE:</b>        | High Power ED  | <b>MACADAM ELIPSE:</b>            | 3-Step         |
| <b>MAXIMUM WATTAGE:</b>     | 2W             | <b>UGR:</b>                       | To Be Advised  |
| <b>MAXIMUM LAMP LENGTH:</b> | Not Applicable | <b>BEAM ANGLE:</b>                | Not Applicable |
| <b>LAMP INCLUDED?</b>       | Yes (Integral) | <b>TILT ADJUSTMENT ANGLE:</b>     | Not Applicable |
| <b>LUMINOUS FLUX:</b>       | 70 (lm)        | <b>ROTATION ADJUSTMENT ANGLE:</b> | Not Applicable |
| <b>COLOUR TEMP:</b>         | 2700 (K)       | <b>AVERAGE LIFESPAN:</b>          | 60,000 (Hrs)   |
| <b>CRI:</b>                 | 80             | <b>L70:</b>                       | To Be Advised  |
| <b>R9:</b>                  | 6.9            |                                   |                |

### ELECTRICAL

|                               |                        |                                 |                |
|-------------------------------|------------------------|---------------------------------|----------------|
| <b>SWITCHED:</b>              | No                     | <b>SUPPLY FREQUENCY:</b>        | Not Applicable |
| <b>DIMMABLE:</b>              | Yes                    | <b>DRIVER/BALLAST VOLTAGE:</b>  | Not Applicable |
| <b>DIMMING METHOD:</b>        | Control Gear Dependant | <b>DRIVER AVERAGE LIFESPAN:</b> | Not Applicable |
| <b>DRIVER OUTPUT CURRENT:</b> | Not Applicable         | <b>EFFICACY:</b>                | 17.07 (lm/W)   |
| <b>DRIVER OUTPUT VOLTAGE:</b> | Not Applicable         | <b>DRIVER/BALLAST INCLUDED?</b> | Not applicable |

## ADDITIONAL INFORMATION

Product tested with 1836 - LED Driver CC 250/350/500/700mA DALI Dim



BOX QUANTITY x 16



# PRODUCT ELEVATIONS

---

