

Product Code 25-7742-05-05 Installation Instructions 3D File Photometry Dialux | ULD Revit (BIM)





Benedito Design

Floor lamp H LED 27.7 LED warm-white 2700K ON-OFF Black 1207lm

#### Technical features

Luminaire total power: 27.7W

Real lumens: 1207 Real Im/W: 44

Correlated Colour Temperature (CCT): LED warm-white 2700K

Lens / reflector angle: HORIZONTAL 142°

Structure material: Steel Structure finish: Black Diffuser material: Acrylic Diffuser finish: Sandblasted **Driver Brand: TRIDONIC** 

Voltage / frequency: 220-240V/50-60Hz

Dimming protocol: ON-OFF

Power Factor: 0.90

Useful life: 50,000h L80B20

Warranty: 5 años











### Luminotechnic features

CRI: 90

MacAdam steps: 3

Photobiological risk: RG2 UGR crosswise: 22.3 UGR lengthwise: 22.3

Lampholder	Quantity	Light source power (W)
		perrer (11)
LED	1	25.2W








Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.

# LedsC4

Product Code 25-7742-05-05

Installation Instructions
3D File
Photometry
Dialux | ULD
Revit (BIM)



 $\mathbf{H}$ 

Benedito Design

Floor lamp H LED 27.7 LED warm-white 2700K ON-OFF Black 1207lm

### Logistics



Net weight (kg): 7.27

Packaged weight (kg): 10.6

Packaging: 1490mm x 440mm x

450mm

## Light application



Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.