

Gea LED Signaling ø45mm Recessed uplighting

Designer: LEDS C4



**Description**

Floor recessed for outdoor use.

For uplighting. Includes flush-mounting box. Includes filters to emulate warm light. Includes filter to create diffuse light. Specially designed to conceal all mounting screws. Suitable for installation in marine environments. Cable meters included: 2.5. Maximum light surface temperature below 40°C. Structure material: Aluminium. Structure finish: Anodized. Diffuser material: Glass. Diffuser finish: Matt. UV protection. Warranty: 5 Years.

**Finish**  
Anodized  
Matt

**Material**  
Aluminium  
Glass

IP65/IP67 IK05   36

**TECHNICAL CHARACTERISTICS**

**Light source**

Light source: LED REFOND  
Output (W): 0.5W  
Total power consumption (W): 0.5  
Color temperature: LED neutral-white 4000K  
CRI: 70  
Photobiological risk: RG0  
Real Lumen: 12  
Qty Leds: 6  
Lm/Real W: 24  
Life Time: 50.000h L80B20  
Bin / Grup: NK1 o NK2  
MacAdam steps: 3  
UGR: 20.6

**GEAR**

This item requires gear. It is not included.

**Luminaire**

Temperature on the surface: 40.00  
Double cable exit: No  
Drainage: Yes  
Public Areas: 1000  
Seaside: Yes  
Cable meters included: 2.5  
Uv Protection: Yes  
Warranty: 5 Years

**Logistics**

Energy Efficiency: LED A++  
EAN Code: 8435381412487  
Net Weight (Kg): 0.220  
Weight in Kg (packaged): 0.290  
Packing: 75 x 75 x 200  
Masterbox: 36

The photograph may not match the reference exactly. Please read the product description to identify the finish.