

Gigo Outdoor Wall light Fitting

INSTRUCTION MANUAL

Safety Warnings

- This product is only suitable for connection to a 240V~50Hz supply in accordance with current IEE wiring regulations. It should be installed in accordance with local building regulations and is for domestic use only.
- Before commencing installation of your light fitting always switch off the mains supply and remove the appropriate fuse or switch off the appropriate circuit breaker.
- This is a Class I product, and **must** be Earthed. The terminal blocks are supplied according to requirements of the fitting.
- Run supply wire from a 5-amp electrical supply protected by an RCD using double insulated 3-core cable of type H05RN-F 1.0mm² (not supplied) to selected site, ensuring it is adequately protected through the full length of the cable run, it must come out of the flat surface of the wall or steps in line with the entry to the fitting.
- Except where installed in a conduit or duct which provides equivalent protection against mechanical damage, a cable buried in the ground shall incorporate an earthed armour or metal sheath or both, suitable for use as a protective conductor, or be of insulated concentric construction. Buried cables shall be marked by cable covers or a suitable marking tape. Buried conduits and ducts shall be suitably identified. Buried cables, conduits and ducts shall be at a sufficient depth to avoid being damaged by any reasonably foreseeable disturbance of the ground.
- Never fit bulbs of a higher wattage than those specified on the label, as these may cause overheating and damage the fitting.
- This product is suitable for outdoor use, has special protection against the ingress of water, and is rated IP55.
- If you are in any doubt about your competence please consult a qualified electrician.
- If any modification is made it will invalidate the warranty and may render the product unsafe.
- If any part of the glass is broken or cracked then it must be replaced immediately to preserve the water ingress protection.

Care Information

Allow 10 minutes to cool before replacing, adjusting or cleaning.

Clean with a dry cloth only. Do not use liquid or abrasive cleaners on this product.

Assembly/ User Instructions

Before you start

Please read these instructions carefully before fitting and retain for reference. Check the packaging and make sure that you have all the required parts. Follow each assembly step in order to prevent incorrect assembly. Ensure that the product is fully assembled as illustrated before use.

DO NOT CONNECT THIS PRODUCT TO A DIMMER SWITCH / EXTERNAL PIR UNIT.

The Light pack contains:

Light fitting.
Terminal connection block.
Fixing pack.

The following tools may be required:

Selection of cross and flat head screwdrivers.
Electric drill and assorted drill bits.
Wire strippers.
Electrical insulation tape.

These assembly diagrams are intended as a guide – if in doubt consult a qualified electrician.

1. Decide on the position of the light fitting, or remove existing light fitting. Note the position of the electrical connections. Ensure there is a solid mounting surface, preferably a brick wall, to support the weight of the light fitting.
2. Detach the back plate (A) from the product by removing the screws and screw covers from the front of the fitting (B). There are four screws to remove. Keep them safe for refitting later
3. Use the back plate as a template to mark the screw holes, and secure to the wall with appropriate screw fixings (C), making sure the back plate is correctly aligned. Take care to avoid damaging any concealed wiring or pipes.

Assembly/ User Instructions Continued

4. Bring the mains cable through the rubber grommet. Connect the house wiring to the internal terminal block (D) – see expanded wiring details below. **NOTE: This is a Class I fitting and must be earthed.** The cable entry grommet must be securely in place to ensure that the water ingress protection is maintained.
5. Fit the front frame over the back plate and secure with the four screws. Take care not to trap or strain the internal cables. Place the caps over the four screws.
6. Fit the LED GU10 lamps - not supplied. **NOTE: Never fit bulbs of a higher wattage than those specified on the label as these may cause overheating and damage the fitting.**
7. Fit the covers over the lamps.
8. Turn on the power and test.

