


Floodlight

XLED home 2

EAN 4007841033088



Functional description

The moveable sensor-switched outdoor floodlight with fully swivelling LED panel in a classy opal look. The XLED home 2 sensor-switched floodlight comes in a sophisticated design. It is not just an eye-catcher, but also a truly talented mover. Thanks to the fully swiveling LED panel, every corner of the entrance area can be illuminated flexibly and as required. The highly efficient LED technology coupled with the opal cover provides maximum lighting comfort. As an individual floodlight or interconnected with the slave version, the innovative new generation of the XLED home success series is available in white, black, graphite and silver.

Technical specifications

Luminous flux	1184 lm
Output	14,8 W
Light colour	4000 K / SDCM 3
Detection angle	140° with sneak-by protection
Reach	14 m
Floodlight positioning range	180° horizontally, 180° vertically
Sensor swivelling range	180 °
Sensor tilting range	90 °
Sensor type	Passive infrared
Dimensions(w x h x d):	194 x 180 x 161 mm
Voltage	230 - 240 V, 50 Hz/60 Hz
Mains power	75 mA
Power factor	0.84
Max. Output	Max. 1000 W, max. 4 fluorescent lamps / LED lamps, C < 88 µF
Efficiency	80 lm/W
Colour rendering	Ra ≥ 80
LED cooling system	HCMC (High Conductive Magnesium Composite)
LED life expectancy	50,000 h (L70B10 to LM80)
Capability of masking out individual segments	Yes
Time setting	8 sec. - 35 min.
Degree of protection (IP)	IP44
Protection class	II
Material	UV-resistant plastic
Temperature range	-20°C - +40°C
With lamp	STEINEL LED system
Lamp replaceable	No
Version	White