

# MASHIKO 400 ROUND 7421

SKU 1121026

astro



## PRODUCT SPECIFICATION

### GENERAL

|                                  |                                                 |                        |                                                  |
|----------------------------------|-------------------------------------------------|------------------------|--------------------------------------------------|
| <b>FINISH:</b>                   | Polished Chrome                                 | <b>CABLE LENGTH:</b>   | Not Applicable                                   |
| <b>MAIN MATERIAL:</b>            | Metal - Stainless Steel                         | <b>GROSS WEIGHT:</b>   | 4.16 (kg)                                        |
| <b>DIMENSIONS:</b>               | H:100mm Ø:400mm                                 | <b>CLASS:</b>          | CE (Class II)                                    |
| <b>INSTALLATION ORIENTATION:</b> | Ceiling mount<br>Wall mount (reduced IP rating) | <b>IP RATING:</b>      | IP44                                             |
| <b>CUT OUT HOLE:</b>             | Not Applicable                                  | <b>BATHROOM ZONE:</b>  | Zone 2, 3                                        |
| <b>RECESS DEPTH:</b>             | Not Applicable                                  | <b>VOLTAGE:</b>        | Mains 230v                                       |
| <b>FIRE RATING:</b>              | Not Applicable                                  | <b>PRODUCT F MARK:</b> | Not suitable for mounting on flammable materials |

### LAMP

|                             |                          |                                   |                |
|-----------------------------|--------------------------|-----------------------------------|----------------|
| <b>LIGHT SOURCE:</b>        | E27/ES                   | <b>MACADAM ELIPSE:</b>            | Not Applicable |
| <b>MAXIMUM WATTAGE:</b>     | 3 x 42W Max              | <b>UGR:</b>                       | Not Applicable |
| <b>MAXIMUM LAMP LENGTH:</b> | 170 (mm) / 6.69 (inches) | <b>BEAM ANGLE:</b>                | Not Applicable |
| <b>LAMP INCLUDED?</b>       | No                       | <b>TILT ADJUSTMENT ANGLE:</b>     | Not Applicable |
| <b>LUMINOUS FLUX:</b>       | Lamp Dependent           | <b>ROTATION ADJUSTMENT ANGLE:</b> | Not Applicable |
| <b>COLOUR TEMP:</b>         | Lamp Dependent           | <b>AVERAGE LIFESPAN:</b>          | Lamp Dependent |
| <b>CRI:</b>                 | Lamp Dependent           | <b>L70:</b>                       | Not Applicable |
| <b>R9:</b>                  | Lamp Dependent           |                                   |                |

### ELECTRICAL

|                               |                |                                  |                |
|-------------------------------|----------------|----------------------------------|----------------|
| <b>SWITCHED:</b>              | No             | <b>SUPPLY FREQUENCY:</b>         | Not Applicable |
| <b>DIMMABLE:</b>              | Yes            | <b>DRIVER / BALLAST VOLTAGE:</b> | Not Applicable |
| <b>DIMMING METHOD:</b>        | Lamp Dependent | <b>DRIVER AVERAGE LIFESPAN:</b>  | Not Applicable |
| <b>DRIVER OUTPUT CURRENT:</b> | Not Applicable | <b>EFFICACY:</b>                 | Lamp Dependent |
| <b>DRIVER OUTPUT VOLTAGE:</b> | Not Applicable | <b>DRIVER INCLUDED?</b>          | Not applicable |

## ADDITIONAL INFORMATION



BOX QUANTITY X4

# PRODUCT ELEVATIONS

---

