





## Prolix Surface

Nahrang Design

## 00-8513-DN-DN

Pendant Prolix Surface LED 5.9W LED warm-white 2700K PHASE CUT Matte gold 217lm



### TECHNICAL FEATURES

IP20



Total power consumption of light (W) : 7.6W

Driver Brand : HEP

Real lumens : 217

Voltage / frequency : 220-240VAC/50-60Hz

Real lm/W : 29

Dimming protocol : PHASE CUT

Correlated Colour Temperature (CCT) : LED warm-white 2700K

Power Factor : 0.96

Useful life : 50.000h L80B20

Lens / reflector angle : FLOOD 48°

Warranty : 5 Years

UGR : <=16

Structure material : Aluminium

Structure finish : Matte gold

Diffuser material : Methacrylate

Diffuser finish : Transparent

### LUMINOTECHNIC FEATURES

Luminance C0°G65°: 275

Luminance C90°G65°: 275

TM30 RG: 100

TM30 RF: 91

Melanopic ratio: 0.510

UGR

UGR crosswise: 5.6

UGR lengthwise: 5.6

UGR	
S=0.250	
Ceiling / cavity	0.7
Walls	0.5
Working Plane	0.2
Room dimensions	X=4H, Y=8H
UGR crosswise	5.6
UGR lengthwise	5.6

Lampholder	Quantity	Light source power (W)
LED	1	5.9W

### LOGISTICS

Net weight (kg): 0.55

Packaged weight (kg): 0.68

Packaging: 235mm x 130mm x 90mm



